

Please read below before starting.

In The Box

1x AX-Mini 4



1x AX-BALTX



1x Power supply

With country specific lead



1x SIR2 IR emitter



The AX-Mini 4 is ready to go right out of the box with no programming required. However if any custom control is required using either the built-in IR output, R1D/R4D controllers, KPD keypads or the KPC2.8 touch screens, then the Axiom Design Portal Software must be used to create the custom design and programming.

Getting started

The Axiom AX-Mini 4's small profile allows it to be installed in virtually any location (you are no longer bound by a AV rack location!) and in any construction type, be it a new build or existing. The AX-Mini 4 uses industry standard wiring runs.; Speaker wire, network cables, keypad cables and audio source cables should be **home** run to the AX-Mini 4 installation location.

1. Connect speakers to the zone output phoenix connectors

Each zone is rated at 30watts. A maximum of two speakers per-zone @8Ω should be connected.

One zone can be run @4Ω.

For areas that require multiple speakers simply link 2 or more zones via the **configuration setup page**. A maximum of 32 zones (8x Mini 4's) can be connected in any one system.

2. Connect the Mini 4 to the network via the Ethernet port

Connect the AX-Mini 4 to a Wi-Fi access point via a hardwired Cat5e cable. Internet access is not required for the Mini 4 to work, however for full functionality including Internet media streaming (Pandora and TuneIn) and system firmware updates internet access will be required.

3. Connect analog input sources

Source 1 local input is connected via RCA. Source 2 is connected via Cat5e and the AX-BALTX, this source can be connected up to 300ft (100m) away from the AX-Mini 4. IR commands can also be transmitted to the source device, this is programmed through the Axiom Portal Software. A free download is available at www.axium.co.nz

4. Connect power supply (Use the appropriate power cord for your region)

5. Download the **free** Axiom app for iOS or Android to your device.

(The mobile device must be located on the same network as the AX-Mini 4)


6. Open the Axiom app on your device

The App will automatically discover all the Axiom AX-Mini 4s on your network

Setup is now complete!



Possible Connection Scenario



- 2x Line level inputs
- 2x Streaming Media channels
- 4x Powered Zone outputs
- 2x Digital Coax outputs
- 2x Keypad outputs

PANDORA tunein UPnP


PC network share or NAS drive




Possible Connection Scenario

All sources on each amp available in ANY zone

Upstairs



Down stairs



Tablets and Phones



PC network share
or NAS drive

